

PRESTRESSED CONCRETE SPUN PILES SPECIFICATION

Concrete Compressive Strength $f_c' = 52 \text{ MPa}$ (Cube 600 kg/cm^2)

Size (mm)	Thickness Wall (t)	Cross Section (cm^2)	Section Inertia (cm^4)	Unit Weight (kg/m)	Class	Bending Moment		Allowable Compression (ton)	Decompression Tension (ton)	Length of Pile ** (m)
						Crack * (ton.m)	Ultimate (ton.m)			
300	60	452.39	34,607.78	113	A2	2.50	3.75	72.60	23.11	6-12
					A3	3.00	4.50	70.75	29.86	6-13
					B	3.50	6.30	67.50	41.96	6-14
					C	4.00	8.00	65.40	49.66	6-15
350	65	581.98	62,162.74	145	A1	3.50	5.25	93.10	30.74	6-13
					A3	4.20	6.30	89.50	37.50	6-14
					B	5.00	9.00	86.40	49.93	6-15
					C	6.00	12.00	85.00	60.87	6-16
400	75	765.76	106,488.95	191	A2	5.50	8.25	121.10	38.62	6-14
					A3	6.50	9.75	117.60	45.51	6-15
					B	7.50	13.50	114.40	70.27	6-16
					C	9.00	18.00	111.50	80.94	6-17
450	80	929.91	166,570.38	232	A1	7.50	11.25	149.50	39.28	6-14
					A2	8.50	12.75	145.80	53.39	6-15
					A3	10.00	15.00	143.80	66.57	6-16
					B	11.00	19.80	139.10	78.84	6-17
500	90	1,159.25	255,324.30	290	A1	10.50	15.75	185.30	54.56	6-15
					A2	12.50	18.75	181.70	68.49	6-16
					A3	14.00	21.00	178.20	88.00	6-17
					B	15.00	27.00	174.90	94.13	6-18
600	100	1,570.80	510,508.81	393	A1	17.00	25.50	252.70	70.52	6-16
					A2	19.00	28.50	249.00	77.68	6-17
					A3	22.00	33.00	243.20	104.94	6-18
					B	25.00	45.00	238.30	131.10	6-19
800	120	2,563.54	1,527,869.60	641	A1	40.00	60.00	415.00	119.34	6-20
					A2	46.00	69.00	406.10	151.02	6-21
					A3	51.00	76.50	399.17	171.18	6-22
					B	55.00	99.00	388.61	215.80	6-23
1000 ***	140	3,782.48	3,589,571.20	946	A1	75.00	112.50	613.52	169.81	6-22
					A2	82.00	123.00	601.27	215.16	6-23
					A3	93.00	139.50	589.66	258.19	6-24
					B	105.00	189.00	575.33	311.26	6-24
1200 ***	150	4,948.01	6,958,136.85	1,237	A1	120.00	180.00	802.80	221.30	6-24
					A2	130.00	195.00	794.50	252.10	6-24
					A3	145.00	217.50	778.60	311.00	6-24
					B	170.00	306.00	751.90	409.60	6-24
					C	200.00	400.00	721.50	522.20	6-24

Note : *) Crack Moment Based on JIS A 5335-1987 (Prestressed Spun Concrete Piles)
 **) Length of pile may exceed usual standard whenever lifted in certain position
 ***) Type of Shoe for Bottom Pile is Mamira Shoe



TUGAS AKHIR

Nama

Hasbul Wafi
13511188

Dosen Pembimbing

Ir. Suharyatmo, M.,T.

Gambar

Katalog Tiang
Pancang Wika

Skala

1 : 100

Lampiran

10

Data Mutu Beton

box girder (f_c) = 48,9 Mpa
 abutmen (f_c) = 29 Mpa
 pilar (f_c) = 29 Mpa

Data Mutu Baja

D > 12 mm (f_y) = 240 Mpa
 D < 12 mm (f_y) = 400 Mpa
 Baja Prategang (f_{pu}) = 1860 Mpa
 (f_{py}) = 1676 Mpa